

JAMMB SHACKLES

PATENTED TECHNOLOGY



Experience has shown that the kiln chain area the actual temperatures are approx. 100-150°C (212-302°F) lower than in the kiln centre, therefore, a lower heat resisting grade for shackles and hangers is recommended and more cost effective.

- Reduces dust generation by up to 50% over common sizes of round link chain
- Twice the surface area per link compared to 3/4" x 3" roundlink chain
- Half the required links means reduced installation Cost
- Proprietary Alloys for optimized chain link life
- Often less than 12 month Return-On-Investment

Diameter															weight	drawing	
D		D1		a		b		c		d		e		f		kg	
mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch		
19	3/4	19	3/4	95	3 3/4	50	2	34	1 11/32	22	7/8	14	9/16	45	1 3/4	0,75	1216/1782
22	7/8	22	7/8	100	4	55	2 5/32	36,5	1 7/16	26	1	16	5/8	52	2 1/16	1,05	9471120
27	1 1/10	22	7/8	95	3 3/4	50	2	27		26		20	3/8	48		1,30	977556
24	15/16	20	3/4	93	3 5/32	48	1 57/64	27	1 1/16	26	1 1/64	20	3/4	48	1 57/64	1,20	975676
24	15/16	20	3/4	95	3 5/64	46	1 19/16	27	1 1/16	26	1 1/64	20	3/4	48	1 57/64	1,20	3087116
25	1	25	1	102	4	58	2 5/16	38	1 1/2	29	1 5/32	18	23/32	59	2 15/16	1,50	950
25	1	25	1	102	4	58	2 5/16	38	1 1/2	26	1 5/32	18	23/32	59	2 15/16	1,50	950-M 24
25	1	25	1	102	4	58	2 5/16	38	1 1/2	24	1 5/32	18	23/32	59	2 15/16	1,50	950-M 22
25	1	25	1	102	4	58	2 5/16	43	1 1/2	26	1 5/32	18	23/32	59	2 15/16	1,50	950-43-M 24
25	1	20	3/4	100	4	60	3	26	1	26	1	20	3/4	50	2	1,30	3123
25	1	25	1	122		58	2 5/16	45	1 25/32	27,5	1 5/64	22,5	7/8	57	2 1/4	1,70	M5
25	1	25	1	122		58	2 5/16	45	1 25/32	26		22,5	7/8	57	2 1/4	1,70	M 5-Pi 25
25	1	33	1 3/64	92		58	2 5/16	41	1 39/64	27		23	7/8	56	2 13/64	2,00	B 25
28	1 1/8	28	1 1/8	130	3 3/4	70	2 3/4	34	1 3/34	31	1 7/32	27	1 1/16	68	2 49/64	2,00	B 28